

10010596-1

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

**Patent Application for:**

**Mechanical Interface for Rapid Replacement of RF Fixture Components**

**Inventors:** Helmuth O. Kroog  
Timothy A. Lock  
William R. Miner  
Grant E. Cashen  
Mark Stauder

**Docket Number:** 10010596-1

**PATENT**

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26

**Mechanical Interface for Rapid Replacement of RF Fixture Components**

**TECHNICAL FIELD**

This invention relates generally to the field of radio frequency (RF) test and measurement systems, and more specifically to the mechanical components useful for test and measurement within RF enclosures.

**BACKGROUND OF THE INVENTION**

RF sealing is employed in test and production environments where the amount of radiation emitted or absorbed by an electronic device must be closely controlled. Excess RF exposure can lead to erroneous test results, or in production and operational environments, degrade the performance of equipment sensitive to the emitted radiation. RF sealing is also important when an electronic component emits sufficient radiation to impact the performance of other proximate electronic components. In this second case, RF sealing isolates the source of radiation, while the first case may be used to isolate sensitive RF components.

RF enclosures may be used in a variety of test and measurement applications when the amount of RF radiation that impacts a device under test (DUT) must be carefully controlled. Specific examples include prototype testing and production testing of cellular telephones, portable computers, pagers, and

1 other small electronic devices. Often RF enclosures are used in automated or  
2 semi-automated environments in which machines are used to place the DUT  
3 inside the RF enclosure. In these types of test environments, it is desirable to be  
4 able to evaluate the functionality and correct operation of the DUT while the DUT  
5 is within the RF enclosure. The use of electronics circuitry and software may be  
6 used to apply specific test resources to the DUT and measure the responses. In  
7 most applications, the electronics circuitry and software are located both internal  
8 and external to the RF enclosure. Some of the electronics circuitry located  
9 internal to the RF enclosure, as well as the test functionality being controlled by  
10 the electronics, are specific to a particular type of DUT. An example of this is  
11 isolation testing of cellular phones from different manufacturers. Each phone has  
12 particular testing requirements that necessitate the use of specialized test  
13 functionality. An important issue that arises in the design of an RF fixturing  
14 device is the speed and facility with which device specific resources, also called  
15 customizations, can be replaced. This need to replace customizations can occur  
16 in a production test environment in which the DUT is changed and the RF test  
17 fixture needs to be quickly modified to match the testing requirements of the new  
18 DUT. The need for a quick replacement of device specific resources could also  
19 occur in a production environment when the device specific resources of the RF  
20 test fixture reach the end of their life cycle and fail.

21  
22 The electronics and device specific resources, or customization, are  
23 located on a mechanical support and interface structure. This mechanical  
24 interface structure serves as the primary point of contact between a  
25 customization and the remainder of the RF test fixture. Thus, the need to replace  
26 device specific resources is often translated into the need for a mechanical  
27 interface and the associated interface that is easily replaced.

1 Many solutions exist which allow the replacement of the customization in  
2 an RF test fixture. Typically, these solutions use numerous pneumatic fittings  
3 and expensive custom designed electrical connections to accomplish this. Many  
4 require the user to disconnect pneumatic hoses and/or electrical connections  
5 individually, which adds complexity to the replacement of the customization. This  
6 adds to the time required to replace the customization and also opens the  
7 possibility of making errors in reconnecting the hoses and electrical connections  
8 causing damage to the fixture or customization. Since the interface is complex,  
9 time to develop additional customizations can be excessive. An additional issue  
10 with replacing the customization is creating a strong seal between the  
11 customization and the RF fixture. Prior solutions for making a pneumatic seal in  
12 a removable customization in an RF enclosure have been to use coupling  
13 connectors. These fittings are expensive, require additional parts and machining,  
14 require force to engage, and take up space in the customization.

15  
16 Thus, there is an unmet need in the art for a RF fixturing system that  
17 contains customizations that may be quickly and easily removed, without  
18 disconnecting multiple pneumatic hoses and electrical connections individually.  
19 There is a further need in the art for a mechanical seal interface supporting a  
20 customization that does not require force to engage the seal, and requires very  
21 little space in the customization

1  
2 SUMMARY OF THE INVENTION  
3

4 The RF fixturing system of the present invention allows a plethora of RF  
5 devices to be tested using a standard configuration of electronics components.  
6 Testing different RF devices can be accomplished by changing the type of nest  
7 that is inserted within the RF enclosure. A nest contains RF device specific  
8 functionality. Depending upon the test and measurement requirements, multiple  
9 nests may be present within the RF fixturing system. A RF device is coupled to  
10 the nest within the RF enclosure. The nest contains specific features that allow  
11 the RF device to be properly tested or evaluated.

12  
13 The nest, or "customization", is coupled to a mechanical support structure  
14 that is coupled to the RF fixture within the RF enclosure. Replacing the nest is  
15 facilitated by the design of the mechanical support structure. The mechanical  
16 support structure is designed so that the electrical connections and required  
17 pneumatic hoses are automatically connected as the mechanical support  
18 structure is engaged. So, replacing the nest is reduced to removing the  
19 mechanical support structure with the associated nest and placing a new  
20 mechanical support structure with a new nest.

21  
22 One aspect of quickly replacing the customization is the ability of the  
23 mechanical support structure to quickly create a pneumatic seal with the  
24 mechanical interface of the RF fixture. This seal can be established through the  
25 use of o-rings constrained in a machined groove on a flat plate of the mechanical  
26 interface of the RF fixture. As a flat plate of the mechanical interface for the  
27 customization is placed on top of the mechanical interface of the RF fixture, the  
28 o-rings are sandwiched between the plate of the customization mechanical

interface and the plate of the RF fixture mechanical interface. A fastener is then used to pull the two plates together, thereby creating a seal between the customization and the RF fixture.

# BRIEF DESCRIPTION OF THE DRAWINGS

The features of the invention believed to be novel are set forth with particularity in the appended claims. The invention itself however, both as to organization and method of operation, together with objects and advantages thereof, may be best understood by reference to the following detailed description of the invention, which describes certain exemplary embodiments of the invention, taken in conjunction with the accompanying drawings in which:

**FIG. 1** is a drawing of a RF fixturing device located within an RF enclosure, according to an embodiment of the present invention.

**FIG. 2** is a drawing of a mechanical interface operable to support a customization, according to an embodiment of the present invention.

**FIG. 3** is a drawing of the stationary base assembly, according to an embodiment of the present invention.

**FIG. 4** is a drawing of the lower nest assembly, according to an embodiment of the present invention.

**FIG. 5** is a drawing of the upper nest assembly, according to an embodiment of the present invention.

**FIG. 6** is a drawing of a nest plate and a drawer plate suitable for creating a seal between a customization and an RF fixturing device, according to an embodiment of the present invention.

### DETAILED DESCRIPTION OF THE INVENTION

While this invention is susceptible of embodiment in many different forms, there is shown in the drawings and will herein be described in detail specific embodiments, with the understanding that the present disclosure is to be considered as an example of the principles of the invention and not intended to limit the invention to the specific embodiments shown and described. In the description below, like reference numerals are used to describe the same, similar or corresponding parts in the several views of the drawings.

Referring now to FIG. 1, a drawing of an RF fixturing system 100 comprising a mechanical apparatus 110 located within an RF enclosure 120 is shown according to an embodiment of the present invention. The mechanical apparatus 110 is designed so that one or more types of nests, also called customizations, may be quickly placed within the mechanical apparatus 110. The mechanical apparatus 110 is located within RF enclosure 120, said RF enclosure 120 shielded from RF radiation so that a device under test (DUT) placed within a nest can be accurately tested.

1 Referring now for FIG. 2, a more detailed drawing of the mechanical  
2 apparatus 110 is shown. The mechanical apparatus 110 comprises a stationary  
3 base assembly 210, operable to provide mechanical support to the mechanical  
4 apparatus 110. The stationary base assembly 210 is coupled to a lower nest  
5 assembly 220. The lower nest assembly 220 provides a bottom support for one  
6 or more customizations that can be placed within mechanical apparatus 110.  
7 The lower nest assembly 220 is coupled to an upper nest assembly 230. The  
8 upper nest assembly provides an upper support structure for the one or more  
9 customizations that can be placed within mechanical apparatus 110. It should be  
10 noted that the use of a fixed mechanical apparatus allows a plethora of  
11 customizations to be quickly placed within the mechanical apparatus 110. It is  
12 further noted that more than one mechanical apparatus 110 may be placed within  
13 an RF enclosure, without departing from the spirit and scope of the present  
14 invention.

15  
16 Referring now to FIG. 3, a more detailed drawing of stationary base  
17 assembly 210 is shown, according to a preferred embodiment of the present  
18 invention. The stationary base assembly 210, which provides the foundation for  
19 the mechanical apparatus 110, comprises a left standoff 320, a printed circuit  
20 assembly (PCA) mount 325 coupled to the left standoff 320 and coupled to a  
21 right standoff 330, one or more pneumatic fittings 335 and one or more unused  
22 pneumatic fittings 340 coupled to one of the left standoff 320 and right standoff  
23 330, a base probe plate 345 coupled to the left standoff 320 and the right  
24 standoff 330, two down stops 350 coupled to the corresponding left standoff 320  
25 and right standoff 330, and two guide shafts 355 coupled to the corresponding  
26 two down stops 350. The PCA mount 325 is operable to couple to a nest PCA,  
27 the nest PCA being able to provide test and measurement functionality



1 applicable to a DUT. The two guide shafts 355 provide vertical stability and  
2 alignment to the mechanical apparatus 110.

3  
4 Referring now to FIG. 4, a more detailed drawing of a lower nest assembly  
5 220 is shown, according to a preferred embodiment of the present invention.  
6 The lower nest assembly 220, which provides a mounting location and support  
7 for a DUT, further comprises a DUT support plate 410 coupled to the two guide  
8 shafts 355, a left bearing mount 450 coupled to the DUT support plate 410, a  
9 right bearing mount 460 coupled to the DUT support plate 410, and a pneumatic  
10 supply 420 coupled to the DUT support plate 410 from below. In the preferred  
11 embodiment, the pneumatic supply 420 further comprises one or more  
12 pneumatic fittings 425, a pneumatic cylinder 430, and a coupling nut 435.

13  
14 Referring now to FIG. 5, a more detailed drawing of upper nest assembly  
15 230 is shown. Upper nest assembly 230 is operable to hold one or more test  
16 components that interface with the DUT. Exemplary test components include a  
17 microphone, a speaker, or pneumatic actuators for pushing buttons. Upper nest  
18 assembly 230 further comprises an upper nest plate 510 and a crossbar 520. In  
19 the preferred embodiment of the present invention, the crossbar 520 is coupled  
20 to the upper nest plate 510 by one or more washers 530 and one or more  
21 shoulder screws 540.

22  
23 Referring now to FIG. 6, a side drawing of the base 600 of the mechanical  
24 apparatus 110 is shown. The base 600 comprises a drawer plate 610 coupled to  
25 a nest plate 620. The nest plate 620 is further coupled to the stationary base  
26 assembly 210. The drawer plate 610 comprises one or more locating pins 625  
27 operable to enable the nest plate 620 to be aligned with respect to drawer plate  
28 610, one or more o-rings 630 located in a corresponding one or more circular

10010596-1

1 holes, and one or more pneumatic fittings (not shown in the figure) coupled to  
2 the one or more circular holes from below. The drawer plate 610 further  
3 comprises one or more screw holes 635, said screw holes operable to be  
4 coupled to one or more corresponding fasteners 640 to tightly couple the drawer  
5 plate 610 to the nest plate 620. The nest plate further comprises one or more  
6 screw holes 645 operable to be coupled to the one or more corresponding  
7 fasteners 640.

8  
9 In the preferred embodiment of the present embodiment, when replacing  
10 the mechanical apparatus 110, the one or more locating pins 625, the one or  
11 more fasteners 640, and the one or more screw holes 645 allow a fast coupling  
12 to be established between the drawer plate 610 and the nest plate 620. This fast  
13 coupling is made a tight seal through the use of the one or more o-rings 630.

14  
15 While the invention has been described in conjunction with specific  
16 embodiments, it is evident that many alternatives, modifications, permutations  
17 and variations will become apparent to those of ordinary skill in the art in light of  
18 the foregoing description. Accordingly, it is intended that the present invention  
19 embrace all such alternatives, modifications and variations as fall within the  
20 scope of the appended claims.

21  
22 What is claimed is:  
23